

**GERO<sup>®</sup>therm Y piece kit (pipe joint)**

Y piece kit for joining the two forward and return flows of a double U geothermal probe into one outlet each, injection-moulded from PE100-RC black, **PN16**, mass and quality requirements according to DIN 8074/8075, production and testing according to guideline HR 3.26 of the SKZ Würzburg plastics centre, for welding using electrofusion, heated tool socket or butt welding in accordance with DVS 2207; with attached electrofusion coupler socket.  
1 unit packed in each bag.

Pipe dimensions: d 32-32-40  
Two-sided electrofusion coupler socket  
Art. No.: 104837  
Quantity: ..... Units

Pipe dimensions: d 32-32-40  
Single-sided electrofusion coupler socket  
Art. No.: 104838  
Quantity: ..... Units

Pipe dimensions: d 40-40-50  
Two-sided electrofusion coupler socket  
Art. No.: 104839  
Quantity: ..... Units

Pipe dimensions: d 40-40-50  
Single-sided electrofusion coupler socket  
Art. No.: 104840  
Quantity: ..... Units

**GERO<sup>®</sup>therm Y piece (pipe joint)**

Y piece for joining the two forward and return flows of a double U geothermal probe into one outlet each, injection-moulded from PE100-RC black, **PN16**, mass and quality requirements according to DIN 8074/8075, production and testing according to guideline HR 3.26 of the SKZ Würzburg plastics centre, for welding using electrofusion, heated tool socket or butt welding in accordance with DVS 2207. 2 unit packed in each bag.

Pipe dimensions: d 32-32-40  
Art. No.: 104201  
Quantity: ..... Units

Pipe dimensions: d 40-40-50  
Art. No.: 104202  
Quantity: ..... Units

**GERO<sup>therm</sup>® Y piece kit PE100-RT-RC (pipe joint)**

Y piece kit for joining the two forward and return flows of a double U geothermal probe into one outlet each, injection-moulded from PE100-RT-RC red, **SDR11**, mass and quality requirements according to DIN 8074/8075, production and testing according to guideline HR 3.26 of the SKZ Würzburg plastics centre, for welding using electrofusion, heated tool socket or butt welding in accordance with DVS 2207; with attached electrofusion coupler socket. 1 unit packed in each bag.

Pipe dimensions: d 32-32-40 mm

Two-sided electrofusion coupler socket

Art. No.: 104841

Quantity: ..... Units

Pipe dimensions: d 32-32-40 mm

Single-sided electrofusion coupler socket

Art. No.: 104842

Quantity: ..... Units

Pipe dimensions: d 40-40-50 mm

Two-sided electrofusion coupler socket

Art. No.: 108541

Quantity: ..... Units

Pipe dimensions: d 40-40-50 mm

Single-sided electrofusion coupler socket

Art. No.: 104843

Quantity: ..... Units

**GERO<sup>therm</sup>® Y piece PE 100-RT-RC (pipe joint)**

Y piece for joining the two forward and return flows of a double U geothermal probe into one outlet each, injection-moulded from PE100-RT-RC red, **SDR11**, mass and quality requirements according to DIN 8074/8075, production and testing according to guideline HR 3.26 of the SKZ Würzburg plastics centre, for welding using electrofusion, heated tool socket or butt welding in accordance with DVS 2207. 2 unit packed in each bag.

Pipe dimensions: de 32-32-40 mm

Art. No.: 104787

Quantity: ..... Units

Pipe dimensions: de 40-40-50 mm

Art. No.: 104788

Quantity: ..... Units