



Object: _____
 Customer: _____
 Contact person: _____

Total flow rate: _____ m³/h

Sizing Collector/Distributor:

- ☐ SAVE 97 ≤ 7.9 m³/h*
- ☐ SAVE 125 ≤ 19.6 m³/h*
- ☐ SAVE 180 ≤ 48.4 m³/h*
- ☐ SAVE 250 ≤ 118.4 m³/h*

Collector/distributor
 Number of connections 37+ pcs:
 (e.g. 37 pcs = 37x flow + 37x return)

Connections ☐ Ø 32
☐ Ø 40
☐ Ø 50

Main outlet outer diameter: Ø _____ mm

Flow-collector, from the probe:
 (in accordance with SIA)

☐ Inline-Setter (5-42 l/min)
☐ Inline-Setter (20-70 l/min)
☐ Hyline-Setter (10-25 l/min)
☐ Hyline-Setter (20-60 l/min)
☐ Ball valve

Return-distributor, to the probe:
 (in accordance with SIA)

☐ Ball valve

Air vent:
 Butterfly valve for main outlet:

☐ Autom. ☐ Manual ☐ No
☐ Yes ☐ No

Cover (class):

☐ A15 bolted
☐ B125 bolted
☐ D400 supplied loose

Options:
☐ Thermomanometer
☐ Lighting tube lamp

☐ Dome sealing against groundwater
☐ Level adjustment on site
 * \dot{V} max. [m³/h] @ 1m/s