



**Technical data sheet**

**GEROtherm® SAVE**

---

SAVE 125 collector/distributor

## GEROthem® SAVE 125 collector/distributor

General properties	
Collector/distributor design	GEROthem® collector/distributor made of PE100-RC, with a silvery surface, PN16 for connecting the geothermal probes and feeding to the heat pump. Weld seams made in accordance with DVS, quality monitoring in accordance with the directive HR3.26 of the Süddeutsches Kunststoffzentrum (SKZ) Würzburg/Germany. Minimal flow resistances. Specially developed for geothermal use.
Components	<ul style="list-style-type: none"> <li>▪ Main body d125/83.4 mm</li> <li>▪ Flat-sealing ball valves, type GF375 with pipe sockets PE100-RC, PN16</li> <li>▪ Balancing valves, inline setter or hyline setter</li> <li>▪ Optionally with or without filling/drain cock</li> <li>▪ 3 socket Rp ½" IT for thermometers, deaerators and left / right use</li> <li>▪ Discharge with external thread or as PE socket</li> </ul>
Application	Combination of several geothermal probes for a feed and return line to the heat pump
Flow rate range	Maximum 19.6 m³/h (at 1 m/s flow velocity in the main body of the collector/splitter)
Main discharge (selectable)	<ul style="list-style-type: none"> <li>▪ PE socket PN 16 dn 63/75/90/125 mm</li> <li>▪ Loose flange: Ø 63/75/90/110 / 125mm</li> <li>▪ External thread 2" / 2 ½"</li> <li>▪ internal thread 2"</li> </ul>
Connection dimensions:	dn ø 40 mm dn ø 50 mm
Balancing valves inline setter	5–42 l/min; 8–30 l/min; 20–70 l/min (freely selectable)
Balancing valves hyline setter	10–25 l/min; 20–60 l/min (freely selectable)
Delivery form	Up to five connections as a package. From six connections on a wooden pallet.
Product standards	SIA 384/6:2012; SKZ HR3.26
External monitoring	Süddeutsches Kunststoffzentrum (SKZ), Würzburg/Germany
Physical properties	
Material (main body)	Polyethylene PE100-RC black/silver
Density	0.95–0.97 g/cm³
Pipe roughness	0.03 mm
Mechanical properties	
Mean coefficient of linear thermal expansion	0.18 mm/m K
Thermal properties	
Maximum operating temperature (at maximum 3 bar)	+50°C
Minimum operating temperature	0°C
Chemical properties	
The HakaGerodur GEROthem® SAVE collectors/distributors are resistant to the common heat transfer media. Refer to the Technical Manual for the suitable heat transfer media.	

Subject to change, 14.11.2023